



Dimension sheet

for filter FS 520

Type	Nominal length	Filter surface m ² gross / net	Quantity of cleaning carriages	Total weight in kg	Quantity of compartments	Quantity of pairs of support
FS 520/ 0,75/ 75	888	102 / 82	1	2810	1x0,75	2
FS 520/ 1,00/ 100	1163	136 / 116	1	3270	1x1,00	2
FS 520/ 1,25/ 125	1493	170 / 150	1	3740	1x0,75 , 1x0,50	2
FS 520/ 1,50/ 150	1768	204 / 184	1	4130	2x0,75	2
FS 520/ 1,75/ 175	2043	238 / 218	1	4490	1x1,00 , 1x0,75	2
FS 520/ 2,00/ 200	2318	272 / 252	1	4760	2x1,00	2
FS 520/ 2,25/ 225	2648	306 / 286	1	5450	3x0,75	2
FS 520/ 2,50/ 250	2923	340 / 320	1	5730	1x1,00 , 2x0,75	2
FS 520/ 2,75/ 275	3198	374 / 354	1	6070	2x1,00 , 1x0,75	2
FS 520/ 3,00/ 300	3473	408 / 388	1	6550	3x1,00	2
FS 520/ 3,25/ 325	3803	442 / 422	1	7310	1x1,00 , 3x0,75	3
FS 520/ 3,50/ 350	4078	476 / 436	2	7780	2x1,00 , 2x0,75	3
FS 520/ 3,75/ 375	4353	510 / 470	2	8140	3x1,00 , 1x0,75	3
FS 520/ 4,00/ 400	4628	544 / 504	2	8680	4x1,00	3
FS 520/ 4,25/ 425	4958	578 / 538	2	9010	2x1,00 , 3x0,75	3
FS 520/ 4,50/ 450	5233	612 / 572	2	9390	3x1,00 , 2x0,75	3
FS 520/ 4,75/ 475	5508	646 / 606	2	9580	4x1,00 , 1x0,75	3
FS 520/ 5,00/ 500	5783	680 / 640	2	10100	5x1,00	3
FS 520/ 5,25/ 525	6113	714 / 674	2	10960	3x1,00 , 3x0,75	3
FS 520/ 5,50/ 550	6388	748 / 708	2	11380	4x1,00 , 2x0,75	3
FS 520/ 5,75/ 575	6663	782 / 742	2	11650	5x1,00 , 1x0,75	4
FS 520/ 6,00/ 600	6938	816 / 776	2	11970	6x1,00	4
FS 520/ 6,25/ 625	7268	850 / 810	2	12500	4x1,00 , 3x0,75	4
FS 520/ 6,50/ 650	7543	884 / 844	2	12860	5x1,00 , 2x0,75	4
FS 520/ 6,75/ 675	7818	918 / 878	2	13150	6x1,00 , 1x0,75	4
FS 520/ 7,00/ 700	8093	952 / 891	3	13740	7x1,00	4
FS 520/ 7,25/ 725	8423	986 / 925	3	14330	5x1,00 , 3x0,75	4
FS 520/ 7,50/ 750	8698	1020 / 959	3	14670	6x1,00 , 2x0,75	4
FS 520/ 7,75/ 775	8973	1054 / 993	3	15040	7x1,00 , 1x0,75	4
FS 520/ 8,00/ 800	9248	1088 / 1027	3	15490	8x1,00	4
FS 520/ 8,25/ 825	9578	1122 / 1061	3	16190	6x1,00 , 3x0,75	4
FS 520/ 8,50/ 850	9853	1156 / 1095	3	16570	7x1,00 , 2x0,75	5
FS 520/ 8,75/ 875	10128	1190 / 1129	3	16900	8x1,00 , 1x0,75	5
FS 520/ 9,00/ 900	10403	1224 / 1163	3	17280	9x1,00	5
FS 520/ 9,25/ 925	10733	1258 / 1197	3	17760	7x1,00 , 3x0,75	5
FS 520/ 9,50/ 950	11008	1292 / 1231	3	18180	8x1,00 , 2x0,75	5
FS 520/ 9,75/ 975	11283	1326 / 1265	3	18530	9x1,00 , 1x0,75	5
FS 520/ 10,00/ 1000	11558	1360 / 1299	4	19040	10x1,00	5
FS 520/ 10,25/ 1025	11888	1394 / 1333	4	19440	8x1,00 , 3x0,75	5
FS 520/ 10,50/ 1050	12163	1428 / 1367	4	20220	9x1,00 , 2x0,75	5
FS 520/ 10,75/ 1075	12438	1462 / 1401	4	20440	10x1,00 , 1x0,75	5
FS 520/ 11,00/ 1100	12713	1496 / 1435	4	20890	11x1,00	5


 Quantity of bags if fully equipped
 Filter size
 Length of the filter bags: 20 = 2,0m
 Quantity of superimposed filter ranges
 Cleaning method: S = clean air
 Product name: F = cassette-type filter


 - Filter housing made of 3mm sheet metal
 - Hood 600mm high and without inserts
 - Without special construction and without ladder

Dimension sheet

for filter FS 522

Type	Nominal length	Filter surface m ² gross / net	Quantity of cleaning carriages	Total weight in kg	Quantity of compartments	Quantity of pairs of support
FS 522/ 0,75/ 75	888	113 / 91	1	2960	1x0,75	2
FS 522/ 1,00/ 100	1163	150 / 128	1	3440	1x1,00	2
FS 522/ 1,25/ 125	1493	188 / 166	1	3930	1x0,75 , 1x0,50	2
FS 522/ 1,50/ 150	1768	225 / 203	1	4340	2x0,75	2
FS 522/ 1,75/ 175	2043	263 / 241	1	4720	1x1,00 , 1x0,75	2
FS 522/ 2,00/ 200	2318	300 / 278	1	5000	2x1,00	2
FS 522/ 2,25/ 225	2648	338 / 316	1	5730	3x0,75	2
FS 522/ 2,50/ 250	2923	375 / 353	1	6020	1x1,00 , 2x0,75	2
FS 522/ 2,75/ 275	3198	413 / 391	1	6380	2x1,00 , 1x0,75	2
FS 522/ 3,00/ 300	3473	450 / 428	1	6880	3x1,00	2
FS 522/ 3,25/ 325	3803	488 / 466	1	7680	1x1,00 , 3x0,75	3
FS 522/ 3,50/ 350	4078	525 / 480	2	8170	2x1,00 , 2x0,75	3
FS 522/ 3,75/ 375	4353	563 / 518	2	8550	3x1,00 , 1x0,75	3
FS 522/ 4,00/ 400	4628	600 / 555	2	9120	4x1,00	3
FS 522/ 4,25/ 425	4958	638 / 593	2	9470	2x1,00 , 3x0,75	3
FS 522/ 4,50/ 450	5233	675 / 630	2	9860	3x1,00 , 2x0,75	3
FS 522/ 4,75/ 475	5508	713 / 668	2	10060	4x1,00 , 1x0,75	3
FS 522/ 5,00/ 500	5783	750 / 705	2	10610	5x1,00	3
FS 522/ 5,25/ 525	6113	788 / 743	2	11510	3x1,00 , 3x0,75	3
FS 522/ 5,50/ 550	6388	825 / 780	2	11950	4x1,00 , 2x0,75	3
FS 522/ 5,75/ 575	6663	863 / 818	2	12240	5x1,00 , 1x0,75	4
FS 522/ 6,00/ 600	6938	900 / 855	2	12570	6x1,00	4
FS 522/ 6,25/ 625	7268	938 / 893	2	13130	4x1,00 , 3x0,75	4
FS 522/ 6,50/ 650	7543	975 / 930	2	13510	5x1,00 , 2x0,75	4
FS 522/ 6,75/ 675	7818	1013 / 968	2	13810	6x1,00 , 1x0,75	4
FS 522/ 7,00/ 700	8093	1050 / 983	3	14430	7x1,00	4
FS 522/ 7,25/ 725	8423	1088 / 1021	3	15050	5x1,00 , 3x0,75	4
FS 522/ 7,50/ 750	8698	1125 / 1058	3	15410	6x1,00 , 2x0,75	4
FS 522/ 7,75/ 775	8973	1163 / 1096	3	15800	7x1,00 , 1x0,75	4
FS 522/ 8,00/ 800	9248	1200 / 1133	3	16270	8x1,00	4
FS 522/ 8,25/ 825	9578	1238 / 1171	3	17000	6x1,00 , 3x0,75	4
FS 522/ 8,50/ 850	9853	1275 / 1208	3	17400	7x1,00 , 2x0,75	5
FS 522/ 8,75/ 875	10128	1313 / 1246	3	17750	8x1,00 , 1x0,75	5
FS 522/ 9,00/ 900	10403	1350 / 1283	3	18150	9x1,00	5
FS 522/ 9,25/ 925	10733	1388 / 1321	3	18650	7x1,00 , 3x0,75	5
FS 522/ 9,50/ 950	11008	1425 / 1358	3	19090	8x1,00 , 2x0,75	5
FS 522/ 9,75/ 975	11283	1463 / 1396	3	19460	9x1,00 , 1x0,75	5
FS 522/ 10,00/ 1000	11558	1500 / 1410	4	20000	10x1,00	5
FS 522/ 10,25/ 1025	11888	1538 / 1448	4	20420	8x1,00 , 3x0,75	5
FS 522/ 10,50/ 1050	12163	1575 / 1485	4	21240	9x1,00 , 2x0,75	5
FS 522/ 10,75/ 1075	12438	1613 / 1523	4	21470	10x1,00 , 1x0,75	5
FS 522/ 11,00/ 1100	12713	1650 / 1560	4	21940	11x1,00	5


Quantity of bags if fully equipped
 Filter size
 Length of the filter bags: 22 = 2,2m
 Quantity of superimposed filter ranges
 Cleaning method: S = clean air
 Product name: F = cassette-type filter


- Filter housing made of 3mm sheet metal
 - Hood 600mm high and without inserts
 - Without special construction and without ladder

Dimension sheet

for filter FS 622

Type	Nominal length	Filter surface m ² gross / net	Quantity of cleaning carriages	Total weight in kg	Quantity of compartments	Quantity of pairs of support
FS 622/ 0,75/ 90	888	135 / 108	1	3100	1x0,75	2
FS 622/ 1,00/ 120	1163	180 / 153	1	3620	1x1,00	2
FS 622/ 1,25/ 150	1493	225 / 198	1	4110	1x0,75 , 1x0,50	2
FS 622/ 1,50/ 180	1768	270 / 243	1	4550	2x0,75	2
FS 622/ 1,75/ 210	2043	315 / 288	1	4970	1x1,00 , 1x0,75	2
FS 622/ 2,00/ 240	2318	360 / 333	1	5290	2x1,00	2
FS 622/ 2,25/ 270	2648	405 / 378	1	6006	3x0,75	2
FS 622/ 2,50/ 300	2923	450 / 423	1	6340	1x1,00 , 2x0,75	2
FS 622/ 2,75/ 330	3198	495 / 468	1	6740	2x1,00 , 1x0,75	2
FS 622/ 3,00/ 360	3473	540 / 513	1	7270	3x1,00	2
FS 622/ 3,25/ 390	3803	585 / 558	1	8070	1x1,00 , 3x0,75	3
FS 622/ 3,50/ 420	4078	630 / 576	2	8600	2x1,00 , 2x0,75	3
FS 622/ 3,75/ 450	4353	675 / 621	2	9010	3x1,00 , 1x0,75	3
FS 622/ 4,00/ 480	4628	720 / 666	2	9610	4x1,00	3
FS 622/ 4,25/ 510	4958	765 / 711	2	9970	2x1,00 , 3x0,75	3
FS 622/ 4,50/ 540	5233	810 / 756	2	10400	3x1,00 , 2x0,75	3
FS 622/ 4,75/ 570	5508	855 / 801	2	10630	4x1,00 , 1x0,75	3
FS 622/ 5,00/ 600	5783	900 / 846	2	11210	5x1,00	3
FS 622/ 5,25/ 630	6113	945 / 891	2	12110	3x1,00 , 3x0,75	3
FS 622/ 5,50/ 660	6388	990 / 936	2	12590	4x1,00 , 2x0,75	3
FS 622/ 5,75/ 690	6663	1035 / 981	2	12910	5x1,00 , 1x0,75	4
FS 622/ 6,00/ 720	6938	1080 / 1026	2	13280	6x1,00	4
FS 622/ 6,25/ 750	7268	1125 / 1071	2	13830	4x1,00 , 3x0,75	4
FS 622/ 6,50/ 780	7543	1170 / 1116	2	14240	5x1,00 , 2x0,75	4
FS 622/ 6,75/ 810	7818	1215 / 1161	2	14580	6x1,00 , 1x0,75	4
FS 622/ 7,00/ 840	8093	1260 / 1179	3	15250	7x1,00	4
FS 622/ 7,25/ 870	8423	1305 / 1224	3	15870	5x1,00 , 3x0,75	4
FS 622/ 7,50/ 900	8698	1350 / 1269	3	16260	6x1,00 , 2x0,75	4
FS 622/ 7,75/ 930	8973	1395 / 1314	3	16680	7x1,00 , 1x0,75	4
FS 622/ 8,00/ 960	9248	1440 / 1359	3	17190	8x1,00	4
FS 622/ 8,25/ 990	9578	1485 / 1404	3	17930	6x1,00 , 3x0,75	4
FS 622/ 8,50/ 1020	9853	1530 / 1449	3	18360	7x1,00 , 2x0,75	5
FS 622/ 8,75/ 1050	10128	1575 / 1494	3	18740	8x1,00 , 1x0,75	5
FS 622/ 9,00/ 1080	10403	1620 / 1539	3	19170	9x1,00	5
FS 622/ 9,25/ 1110	10733	1665 / 1584	3	19680	7x1,00 , 3x0,75	5
FS 622/ 9,50/ 1140	11008	1710 / 1629	3	20150	8x1,00 , 2x0,75	5
FS 622/ 9,75/ 1170	11283	1755 / 1674	3	20550	9x1,00 , 1x0,75	5
FS 622/ 10,00/ 1200	11558	1800 / 1719	4	21120	10x1,00	5
FS 622/ 10,25/ 1230	11888	1845 / 1764	4	21550	8x1,00 , 3x0,75	5
FS 622/ 10,50/ 1260	12163	1890 / 1809	4	22400	9x1,00 , 2x0,75	5
FS 622/ 10,75/ 1290	12438	1935 / 1854	4	22670	10x1,00 , 1x0,75	5
FS 622/ 11,00/ 1320	12713	1980 / 1899	4	23180	11x1,00	5


 Quantity of bags if fully equipped
 Filter size
 Length of the filter bags: 22 = 2,2m
 Quantity of superimposed filter ranges
 Cleaning method: S = clean air
 Product name: F = cassette-type filter


 - Filter housing made of 3mm sheet metal
 - Hood 600mm high and without inserts
 - Without special construction and without ladder

Dimension sheet

for filter FS 722

Type	Nominal length	Filter surface m ² gross / net	Quantity of cleaning carriages	Total weight in kg	Quantity of compartments	Quantity of pairs of support
FS 722/ 0,75/ 105	888	158 / 127	1	3250	1x0,75	2
FS 722/ 1,00/ 140	1163	210 / 179	1	3810	1x1,00	2
FS 722/ 1,25/ 175	1493	263 / 232	1	4300	1x0,75 , 1x0,50	2
FS 722/ 1,50/ 210	1768	315 / 284	1	4770	2x0,75	2
FS 722/ 1,75/ 245	2043	368 / 337	1	5220	1x1,00 , 1x0,75	2
FS 722/ 2,00/ 280	2318	420 / 389	1	5570	2x1,00	2
FS 722/ 2,25/ 315	2648	473 / 442	1	6300	3x0,75	2
FS 722/ 2,50/ 350	2923	525 / 494	1	6600	1x1,00 , 2x0,75	2
FS 722/ 2,75/ 385	3198	578 / 547	1	7090	2x1,00 , 1x0,75	2
FS 722/ 3,00/ 420	3473	630 / 599	1	7660	3x1,00	2
FS 722/ 3,25/ 455	3803	683 / 652	1	8460	1x1,00 , 3x0,75	3
FS 722/ 3,50/ 490	4078	735 / 672	2	9060	2x1,00 , 2x0,75	3
FS 722/ 3,75/ 525	4353	788 / 725	2	9490	3x1,00 , 1x0,75	3
FS 722/ 4,00/ 560	4628	840 / 777	2	10120	4x1,00	3
FS 722/ 4,25/ 595	4958	893 / 830	2	10470	2x1,00 , 3x0,75	3
FS 722/ 4,50/ 630	5233	945 / 882	2	10950	3x1,00 , 2x0,75	3
FS 722/ 4,75/ 665	5508	998 / 935	2	11210	4x1,00 , 1x0,75	3
FS 722/ 5,00/ 700	5783	1050 / 987	2	11820	5x1,00	3
FS 722/ 5,25/ 735	6113	1103 /1040	2	12720	3x1,00 , 3x0,75	3
FS 722/ 5,50/ 770	6388	1155 /1092	2	13230	4x1,00 , 2x0,75	3
FS 722/ 5,75/ 805	6663	1208 /1145	2	13590	5x1,00 , 1x0,75	4
FS 722/ 6,00/ 840	6938	1260 /1197	2	13800	6x1,00	4
FS 722/ 6,25/ 875	7268	1313 /1250	2	14550	4x1,00 , 3x0,75	4
FS 722/ 6,50/ 910	7543	1365 /1302	2	14990	5x1,00 , 2x0,75	4
FS 722/ 6,75/ 945	7818	1418 /1355	2	15360	6x1,00 , 1x0,75	4
FS 722/ 7,00/ 980	8093	1470 /1376	3	16070	7x1,00	4
FS 722/ 7,25/ 1015	8423	1523 /1429	3	16700	5x1,00 , 3x0,75	4
FS 722/ 7,50/ 1050	8698	1575 /1481	3	17120	6x1,00 , 2x0,75	4
FS 722/ 7,75/ 1085	8973	1628 /1534	3	17570	7x1,00 , 1x0,75	4
FS 722/ 8,00/ 1120	9248	1680 /1586	3	18120	8x1,00	4
FS 722/ 8,25/ 1155	9578	1733 /1639	3	18850	6x1,00 , 3x0,75	4
FS 722/ 8,50/ 1190	9853	1785 /1691	3	19320	7x1,00 , 2x0,75	5
FS 722/ 8,75/ 1225	10128	1838 /1744	3	19730	8x1,00 , 1x0,75	5
FS 722/ 9,00/ 1260	10403	1890 /1796	3	20200	9x1,00	5
FS 722/ 9,25/ 1295	10733	1943 /1849	3	20710	7x1,00 , 3x0,75	5
FS 722/ 9,50/ 1330	11008	1995 /1901	3	21220	8x1,00 , 2x0,75	5
FS 722/ 9,75/ 1365	11283	2048 /1954	3	21660	9x1,00 , 1x0,75	5
FS 722/ 10,00/ 1400	11558	2100 /1974	4	22250	10x1,00	5
FS 722/ 10,25/ 1435	11888	2153 /2027	4	22690	8x1,00 , 3x0,75	5
FS 722/ 10,50/ 1470	12163	2205 /2079	4	23580	9x1,00 , 2x0,75	5
FS 722/ 10,75/ 1505	12438	2258 /2132	4	23890	10x1,00 , 1x0,75	5
FS 722/ 11,00/ 1540	12713	2310 /2184	4	24430	11x1,00	5

Quantity of bags if fully equipped
 Filter size
 Length of the filter bags: 22 = 2,2m
 Quantity of superimposed filter ranges
 Cleaning method: S = clean air
 Product name: F = cassette-type filter

- Filter housing made of 3mm sheet metal
 - Hood 600mm high and without inserts
 - Without special construction and without ladder